



GF2 SERIES DIESEL GENERATING SETS

SPECIFICATION

Gensets Model	Rated Output (kw)	Rated Current (A)	Fuel Consumption (g/kw.h)	Starting Method	Engine Model	Dimensions (mm)	N.w. (Kg)
GF2-10KW	10	18.1	≤258.4	12V D.C ELECTRIC	295D	1380x640x1000	600
GF2-12KW	12	21.6	≤258.4	12V D.C ELECTRIC	295D	1380x640x1000	600
GF2-15KW	15	27.1	≤258.4	12V D.C ELECTRIC	395D	1640x650x980	650
GF2-20KW	20	36.1	≤258.4	12V D.C ELECTRIC	495D	1780x750x1000	750
GF2-24KW	24	43.3	≤251.6	12V D.C ELECTRIC	4100D	1780x750x1000	780
GF2-30KW	30	54.1	≤258.4	12V D.C ELECTRIC	495ZD	1820x750x1000	920
GF2-40KW	40	72.2	≤231	24V D.C ELECTRIC	4105ZD	2200x710x1350	1610
GF2-50KW	50	90.2	≤224	24V D.CELECTRIC	4105ZD	2280x820x1350	1750
GF2-64KW	64	115.5	≤224	24V D.CELECTRIC	6105ZD	2400x850x1400	1800
GF2-75KW	75	135.4	≤224	24V D.CELECTRIC	6105ZD	2400x850x1400	2330
GF2-90KW	90	162.5	≤218	24V D.CELECTRIC	6105AZLD	3000x900x1400	2500
GF2-100KW	100	180.5	≤218	24V D.CELECTRIC	6105AZLD	3000x900x1400	2650
GF2-120KW	120	216.6	≤218	24V D.CELECTRIC	6105ZLD	3000x900x1400	2800
GF2-150KW	150	270.7	≤220	24V D.CELECTRIC	6135AZD	3300x960x1650	3500
GF2-200KW	200	361	≤220	24V D.CELECTRIC	6135ZLDR2	3210x1320x1920	3750
GF2-250KW	250	451.2	≤220	24V D.CELECTRIC	6135ZLDU2	3210x1320x1920	3850
GF2-300KW	300	541.5	≤220	24V D.CELECTRIC	J12V2DA	3300x1770x1905	4300
GF2-320KW	320	577.6	≤220	24V D.CELECTRIC	J12V2DAX	3300x1770x1905	4350
GF2-350KW	350	631.7	≤220	24V D.CELECTRIC	KTA19-G3	3400x1900x1900	4720
GF2-400KW	400	722	≤220	24V D.CELECTRIC	KTA19-G4	3400x1900x2300	4950
GF2-500KW	500	902.5	≤220	24V D.CELECTRIC	KT38-G	4336x1900x2310	7300
GF2-600KW	600	1083	≤220	24V D.CELECTRIC	KT38-G2	4690x1800x2400	8300
GF2-800KW	800	1444	≤215	24V D.CELECTRIC	KTA38-G5	4960x1800x2400	9200
GF2-1000KW	1000	1805	≤215	24V D.CELECTRIC	KTA50-G3	5000x1900x2640	10600