

QWSS SERIES SWEAGE PUMPS

WDS(QWSS) stainless steel submersible sewage pump is widely accepted on the market due to its excellent performance. It can pump and drain sewage with suspended solid, and the solid size can be as large as 50mm. This product is able to empty cesspit and pool, process industrial and sanitary waste water, and it is also suitable for the draining of sewage system.

WORKING CONDITIONS

Max Temperature of Fluid up to +80℃
Max Pressure 10bar,
Max Ambient Temperature up to 40℃



QWSS

TECHNICAL DATA

Type	rated flow	Rated head	Power	voltage	Calibre	weight	size
WQD10-10-0.75S	10	10	0.75	220	50	24.2	53X22X27
WQ15-10-0.75S	10	10	0.75	380	50	23.6	53X22X27
WQD15-10-1.1S	15	10	1.1	220	50	25.6	56.5X22X27
WQ15-10-1.1S	15	10	1.1	380	50	25.4	56.5X22X27
WQD15-12-1.5S	15	12	1.5	220	50	26	56.5X22X27
WQ15-12-1.5S	15	12	1.5	380	50	26.8	56.5X22X27
WQ15-20-2.2S	15	20	2.2	380	50	36.1	59X25X29
WQ25-15-2.2S	25	15	2.2	380	65	38.3	59X25X29
WQD40-9-2.2S	40	9	2.2	380	80	40.8	61.5X25X31
WQ50-7-2.2S	50	7	2.2	380	100	43.2	61.5X25X31
WQ15-25-3S	15	25	3	380	50	40	61.5X25X31
WQ25-20-3S	25	20	3	380	60	41.8	61.5X25X31
WQ40-15-3S	40	15	3	380	80	44.3	61.5X25X31
WQ50-10-3S	50	10	3	380	100	47	63.5X27X31
WQ15-32-4S	15	32	4	380	50	39.8	61.5X25X31
WQ25-25-4S	25	25	4	380	65	45.6	63.5X27X31
WQ40-18-4S	40	18	4	380	80	47.8	63.5X27X31
WQ50-15-4S	50	15	4	380	100	21	66X27X32
WQ20-32-5.5S	20	32	5.5	380	50	65.7	71X28X35
WQ30-25-5.5S	30	25	5.5	380	62	68.5	71X28X35
WQ50-18-5.5S	50	18	5.5	380	80	69.7	73X30X37
WQ80-10-5.5S	80	10	5.5	380	100	72.4	73X30X37
WQ100-7-5.5S	100	7	5.5	380	150	84.4	78X35X40
WQ20-40-7.5S	20	40	7.5	380	50	71	71X28X35
WQ30-32-7.5S	30	32	7.5	380	65	72.7	71X28X35
WQ40-22-7.5S	45	22	7.5	380	80	75.4	73X30X37
WQ80-15-7.5S	80	15	7.5	380	100	77.3	73X30X37
WQ100-10-7.5S	100	10	7.5	380	150	88	78X35X40

Standard data and equipment: single phase 220V/50Hz, Brass impeller, carbon steel motor shaft, with motor protector inside.
Others model and material such as three phase, 110V, 60Hz, dual voltage, stainless steel shaft, etc, will be available upon request.